



GasAlert MicroClip XT

multi-gas detector



Multi-gas made simple

The slim and compact GasAlertMicroClip XT provides affordable protection from atmospheric hazards. With the addition of IntelliFlash™, this multi-gas detector offers continuous visual confirmation of detector operation and compliance. Simple one-button operation offers ultimate ease of use and significantly reduces time spent training the user. The GasAlertMicroClip XT is fully compatible with BW's MicroDock II automatic test and calibration system.



H₂S
CO
O₂
LEL

- Continuous visual compliance with IntelliFlash™
- Multi-gas versatility with one-button simplicity
- Incredibly thin and lightweight, making it comfortable to wear
- Extraordinarily low cost of ownership

**WATER
RESISTANT**




BW
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot
- Conveniently manage your fleet using Fleet Manager II

GasAlertMicroClip XT Specifications

Size	4.4 x 2.4 x 1.1 in. / 11.3 x 6.0 x 2.9 cm	
Weight	6 oz. / 171 g	
Temperature	-4 to +136°F / -20 to +58°C	
Humidity	0% - 95% RH (non-condensing)	
Alarms	- Visual, vibrating, audible (95 dB) - Low, High, STEL, TWA, OL (over limit)	
Tests	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)	
Typical battery life	10 hours (typical); recharges in less than 4 hours	
User options	Confidence beep	Combustible gas measurement (% LEL or % by volume methane)
	Set STEL interval	User-settable calibration gas level
	Sensor on/off	Force bump test when overdue
	Latching alarms	Force calibration when overdue
	Safe display mode	Low alarm acknowledge
	Stealth mode	Language choices (five)
	Calibration lock	Set custom start up message
	Auto zero on start up	
	O ₂ auto calibration on start up	
	Set bump test interval	
	IntelliFlash interval	
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC IP 66/67	
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping ATEX: CE  II 1 G Ex ia IIC T4 Ga IECEX: Ex ia IIC T4 Ga CE: European Conformity	
Warranty	Full two-year warranty including all sensors	

Additional GasAlertMicroClip XT features:

- IntelliFlash verifies operation and compliance to both the user and supervisor
- Tamper-proof, one button operation
- Equipped with internal vibrating alarm for high noise areas
- Powered by a lithium polymer battery
- Multi-language support in English, French, German, Spanish and Portuguese

Options and Accessories



MicroDock II compatible



Auxiliary filter kit



IR connectivity kit



Five unit cradle charger


For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications

Gas	Measuring Range	Resolution
H₂S	0-100 ppm	1 ppm
CO	0-500 ppm	1 ppm
O₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm setpoints for all sensors are user adjustable. Setpoints are automatically displayed during instrument start up. Lower resolution for H₂S optional.

Locally available from



European Headquarters

5 Canada Close
Banbury, United Kingdom
OX16 2RT
tel +44 (0) 1295.700.300
fax +44 (0) 1295.700.301

Europe +44 (0) 1295.700.300
France +33 (0) 442.98.17.70
Germany +49 (0) 2137.17.6522
Middle East +971.4.4505852
USA 1.888.749.8878

Latin America +55.11.3475.1873
S.E. Asia +65.6580.3468
China +86.10.6786.7305
Australia +61.3.9464.2770
Other Countries +1.403.248.9226