

LEAK DETECTION SYSTEM

LEAK-MASTER

Micro-leak detection system for packages based on CO₂. LEAK-MASTER features non-destructive detection of the smallest leaks without the need for costly Helium.

Benefits

- minimal response time
- quick product change
- for flexible and rigid packs
- no calibration required
- operator friendly – data and process parameter entry by means of integrated keyboard or remote personal computer (e.g. MS-Excel®)
- easy-to-use intuitive system – no special skills required
- convenient data administration and evaluation for customer oriented quality documentation
- various chamber sizes (see back side)
- easy installation and start-up
- easy to clean splash-proof stainless steel cabinet / housing
- remote transmission of results via Ethernet
- potential free alarm contact for connection of external audible/visual device



Options

- Barcode Reader for simple and quick user/product selection. Available with or without IP-protection. Without IP-protection also available as retrofit version.
- wireless data transmission via WLAN (WIFI)
- stainless steel mobile workstations for various models available

NEW

Product Information

Technical Data

Type	LEAK-MASTER	Vacuum Alarms	max. 50 mbar abs. potential free contact max. 250 V AC or 24 V DC/2 A
Measuring System	ceramic sensor for CO ₂	Interfaces	Ethernet (WLAN optional)
Measuring range	0 ppm - 5000 ppm	Cabinet / Housing	stainless steel, IP 54 (splash-proof)
Resolution	1 ppm	Approvals	Company certified according to ISO 9001:2000 and ISO 14001 CE marked according to: - EMC 89/336/EWG - Low Voltage Directive 73/23/EWG - Machines Directive 98/37/EG
Warm-up time	approx. 10 min.		
Calibration	not required		
Response time of the sensor	approx. 1 sec.		
Leak testing cycle	depends on leak size, CO ₂ -percentage in package, size of chamber		

LEAK DETECTION SYSTEM

Various chamber sizes – from the table model for sample analysing to the mobile bulk compact model for the 100%-analysis of complete packages (e.g. E2-boxes)

Model		Chamber-size approx. in mm (inch) (H x W x D)	Cabinet / housing-size approx. in mm (inch) (H x W x D)	Weight approx. kg	Power consumption kWh	Pump suction capacity m ³ /h	Voltage
	LM 4.2.1 LM 4.2.2	85 x 160 x 365 3.3 x 6.3 x 14.4 85 x 280 x 245 3.3 x 11.0 x 9.6	370 x 330 x 625 14.6 x 13.0 x 24.6	50	0,55	6	230 V AC or 110 V AC
	LM 4.4.1 LM 4.4.2	90 x 345 x 280 3.5 x 13.6 x 11.0 90 x 465 x 160 3.5 x 18.3 x 6.3	395 x 535 x 570 15.6 x 21.1 x 22.4	65	0,55	10	230 V AC or 110 V AC
	LM 4.4.1-S	specifically for bottles up to 1,5 l	395 x 535 x 570 15.6 x 21.1 x 22.4	65	0,55	10	230 V AC or 110 V AC
	LM 5.2.1 LM 5.2.2	100 x 340 x 425 3.9 x 13.4 x 16.7 100 x 460 x 305 3.9 x 18.1 x 12.0	470 x 530 x 700 18.5 x 20.9 x 27.6	85	1,10	21	230 V AC or 110 V AC
	LM 6.0.1 LM 6.0.2	110 x 780 x 350 4.3 x 30.7 x 13.8 110 x 890 x 270 4.3 x 35.0 x 10.6	540 x 975 x 720 21.3 x 38.4 x 28.3	145	1,10	21	230 V AC or 110 V AC
	LM 12.1.1 LM 12.1.2	255 x 595 x 500 10.0 x 23.4 x 19.7 255 x 680 x 415 10.0 x 26.8 x 16.3	1025 x 760 x 855 40.4 x 29.9 x 33.7	225	2,20	100	400 V AC
	LM 12.2.1 LM 12.2.2	165 x 595 x 500 6.5 x 23.4 x 19.7 165 x 680 x 415 6.5 x 26.8 x 16.3	1025 x 760 x 855 40.4 x 29.9 x 33.7	225	1,50	63	400 V AC
	LM 15	225 x 775 x 665 8.9 x 30.5 x 26.2	1200 x 960 x 1080 47.2 x 37.8 x 42.5	285	2,20	100	400 V AC