

GAS ANALYSERS

www.wittgas.com

OXYBABY® M+ for O₂ or O₂/CO₂

Cordless hand held oxygen or combined oxygen and carbon dioxide analyser for checking modified atmospheres in food packs. The ideal instrument for portable, faster and accurate sample tests at the packaging machine, in stores or in laboratories.

OXYBABY® M+ a cost effective mobile alternative to tabletop / fixed analysers.

Ensure that the quality of packaged product is maintained (HACCP), guaranteeing continued customer satisfaction.

The ideal instrument for sample tests with a minimum sample gas requirement, allowing the smallest of modified atmosphere packages (MAP) to be tested.

Integrated data log of the last 100 measurements assigned to specific product names or line numbers.

Benefits

- minimum sample gas requirement for smallest packs
- cordless operation using rechargeable batteries
- simple one hand operation
- easy to clean
- large illuminated graphic display
- multilingual menu guide: German, English, French, Italian, Dutch, Swedish, Finnish, Spanish, Polish, Japanese and Russian
- integrated needle cover to protect the user

Complete in carrying case

- charging device and mains adaptor
- CD-ROM with:
 - operating instructions
- 2 spare needles
- 2 spare filters
- set of 100 rubber seals
- case dimensions (HxWxD): approx. 300x395x105 mm (11.8x15.5x4.1 inch)
- case weight: approx. 1.7 kg

standard version

Other models, options and accessories available on request.

Please identify the individual gases at the time of enquiring!

GAS ANALYSERS

OXYBYBY® M+ O₂
 OXYBYBY® M+ O₂/CO₂

| | | |
|---|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • | Gases | O ₂ balance gas: N ₂ , Ar (others on request) O ₂ and/or CO ₂ balance gas: N ₂ , Ar (others on request) |
| • | • Measuring principle O₂ | electro-chemical cell |
| • | • Measuring principle CO₂ | IR-absorption |
| • | • Sensor lifetime O₂ | approx. 2 years (in air) |
| • | • Sensor lifetime CO₂ | unlimited |
| • | • Measuring range | 0-100%; in 0.1%-steps |
| • | • Sample gas requirement | < 10 ml |
| • | • Sample time | max. 10 sec. |
| • | • Calibration | simple two point calibration |
| • | • Sampling | automatic via needle using integrated pump |
| • | • Data log | last 100 measurements assignment of measurements to different product names or line numbers |
| • | • Multilingual | German, English, French, Italian, Dutch, Swedish, Finnish, Spanish, Polish, Japanese and Russian |
| • | • Temperature (gas/environment) | 5 – 40 °C (41 – 104 °F) |
| • | • Display | backlit |
| • | • Shut down | automatic after 2 minutes of non-use |
| • | • Housing | shock resistant plastic |
| • | • Weight | approx. 600 g (without accessories) |
| • | • Dimensions (HxWxD) | 187 x 106 x 91 mm (7.4 x 4.2 x 3.6 inch) (without needle) |
| • | • Power supply | 2 integrated rechargeable batteries (mains adaptor + charging device included) |
| • | • Charging device | 110 – 240 V AC |
| • | • Approvals | Company certified according to ISO 9001:2000, ISO 14001 and ISO 22000 CE-marked according to: - EMC 2004/108/EC - Low Voltage Directive 2006/95/EC |

Technical Data

Cambridge Sensotec Ltd, Unit 8 Royce Court, St. Ives, CAMBS, PE27 3NE, ENGLAND
 Tel. +44 (0)1480 462142, Fax. +44 (0)1480 466032, sales@Cambridge-Sensotec.co.uk

D9 subject to change